

High-speed performance and application density for
power-managed data centers



IBM System x3550



Highlights

- ***High-performance design to maximize your IT investment***
- ***Manage growth and risk for improved business availability with IBM X-Architecture® features***
- ***Go green and save with new design and tools for optimized power management***

Optimized for speed

Designed for applications ranging from Web serving to workload consolidation and virtualization, the IBM System x3550 offers high-speed, dual-core and quad-core processors with blazing front-side bus speed. Optimized for exceptional application computing, the x3550 features a highly functional infrastructure that addresses more memory, lowers power consumption and provides dramatic systems performance increases.

Innovation comes standard

Standard integrated data protection with hardware RAID and 2.5" SAS hard disk drives keeps your data safe and readily available. Super-efficient network communication and hot-swap redundant power help keep your business humming at lower support costs.

Protect investments, lower heat output

Fault protection comes integrated in the x3550. IBM Systems Director Active Energy Manager™ for x86 delivers advanced control to help monitor power usage and achieve decreased infrastructure, power and cooling costs. Hot-swap, redundant fans keep components cool without taking the server offline.

Select configurations of the x3550 are part of the IBM Express Portfolio™, designed and priced to meet the needs of mid-sized businesses. Reliable and easy to manage, Express models/configurations vary by country.

Get it now

go to **ibm.com/systems/x** or call 1 888 **ShopIBM**
to buy direct or to locate an IBM reseller

x3550 at a glance

Form factor/height	Rack/1U
Processor (max)	Dual-Core Intel® Xeon® Processor 5160 up to 3.0 GHz and up to 1333 MHz front-side bus or Quad-Core Intel Xeon Processor X5460 up to 3.16 GHz and up to 1333 MHz front-side bus
Number of processors (std/max)	1/2
L2 cache	2x2 or 2x6 MB (dual-core) and 2x6 MB (quad-core)
Memory ¹ (std/max)	1 GB or 32 GB Fully Buffered DIMM 667 MHz
Expansion slots	2 PCI-Express (x8) half-length, full-height or optional riser card for 1 PCI-X (64-bit 133 MHz)
Disk bays (total/hot-swap)	2/2 (3.5" form factor) or 4/4 (2.5" form factor)
Maximum internal storage ^{1,2}	600 GB 3.5" hot-swap SAS or up to 2.0 TB simple-swap SATA or 293.6 GB 2.5" hot-swap SAS
Network interface	Integrated dual Gigabit Ethernet
Power supply (std/max)	670W 1/2
Hot-swap components	Power supply, fans, hard disk drives (select models)
RAID support	Integrated RAID-0, -1, -10, optional RAID-5, -6
Systems management	IBM Systems Director Active Energy Manager for x86, Integrated Service Processor, Diagnostic LEDs, drop-down light path diagnostics panel, Automatic Server Restart, optional Remote Supervisor Adapter II SlimLine, IBM Director, IBM ServerGuide™ and optional Remote Deployment Manager
Operating systems supported	Microsoft® Windows Server® 2003, Red Hat Enterprise Linux®, SUSE Linux Enterprise Server, TurboLinux Enterprise Server, Novell NetWare and VMware ESX Server
Limited warranty ³	3-year customer replaceable unit and onsite limited warranty

For more information

World Wide Web

U.S.	ibm.com/systems/x
Canada	ibm.com/ca/en/systems/x
Extended Design Architecture	ibm.com/servers/eserver/ xda/index.html

¹ Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest capacity supported drives available. When referring to variable speed CD-ROMs, CD-Rs, CD-RWs and DVDs, actual playback speed will vary and is often less than the maximum possible.

² GB and TB = 1,000,000,000 and 1,000,000,000,000 bytes, respectively, when referring to storage capacity. Accessible capacity is less.

³ IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services, including those designated as ServerProven® or ClusterProven®.



© Copyright IBM Corporation 2008

January 2008

All Rights Reserved

This publication could include technical inaccuracies or photographic or typographical errors. This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. Consult your local IBM business contact for information on the products or services available in your area.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

IBM, the IBM logo, ClusterProven, Express Portfolio, IBM Systems Director Active Energy Manager, ServerGuide, ServerProven, ServeRAID, System x and X-Architecture are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. For a list of additional trademarks, go to ibm.com/legal/copytrade.shtml.

Intel and Xeon are registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Microsoft, Windows, Windows Server and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.